

Member State of OIML
United Kingdom of Great Britain
and Northern Ireland

OIML Certificate No
R51/2006-GB1-13.01

OIML CERTIFICATE OF CONFORMITY

Issuing authority: **National Measurement Office**

Person responsible: **Paul Dixon – Product Certification Manager**

Applicant: **Actronic Ltd
45 Patiki Road
Avondale, Auckland
New Zealand**

Manufacturer: **The applicant**

Identification of the certified pattern: **L-Series 2180**

This certificate attests the conformity of the above-mentioned pattern (represented by the samples identified in the associated test reports) with the requirements of the following Recommendation of the International Organisation of Legal Metrology (OIML):

OIML R 51 - Edition 2006(E) for accuracy class Y(b)

This certificate relates only to the metrological and technical characteristics of the pattern of the instrument concerned, as covered by the relevant OIML International Recommendation.

This certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the certificates reference number and the name of the OIML Member State in which the certificate was issued, partial quotation of the certificate or of the associated test report is not permitted, though they may be reproduced in full.

Issue Date: 19 March 2013
Reference No: TS0101/0001



Signatory: P R Dixon
for Chief Executive

National Measurement Office | Stanton Avenue | Teddington | TW11 0JZ | United Kingdom
Tel +44 (0)20 8943 7272 | Fax +44 (0)20 8943 7270 | Web www.bis.gov.uk/nmo

NMO is an Executive Agency of the Department for Business Innovation & Skills

The conformity was established by tests and examination described in the associated pattern evaluation report P01061 which includes 12 pages.

Characteristics of the instrument:

This pattern of a battery-operated automatic catchweighing instrument (Category Y), designated the L-Series 2180, comprises an electronic indicator, pressure transducer and sensors mounted on a wheeled loader. This pattern automatically determines the load in the bucket during the lifting process, the hydraulic pressure in the loader's arms is converted by a pressure transducer, the output being used by the indicator to display the corresponding weight.

Construction:

- Pressure transducers: one or two Loadrite model LC965C
- Position reference / Lift speed / Direction sensor: either a Loadrite Model LM960 optical arm-location sensor or a Loadrite Model LR908 spring-loaded rotary encoder type arm-location sensor
- Load receptor ("Bucket") location sensors: Loadrite AAA-20710 sensors
- Inclinator: Loadrite LR966 angle sensor (set to inhibit weighing for a tilt greater than 5°)
- Indicator: Loadrite L2180 weighing indicator console

Devices:

- Semi-automatic zero-setting device ($\leq 4\%$ of Max)

Technical data:

Maximum capacity (Max)	$\leq 350 e$
Scale interval	$1 \text{ kg} \leq e \leq 200 \text{ kg}$
Minimum capacity (Min)	10 e
Pressure transducer	Loadrite Model LC965C
Transducer measuring range	0...350 bar
Transducer output signal	4...20 mA
Climatic environment	-20 °C to +50 °C, open, condensing
Electromagnetic environment	E3
Mechanical environment	Vehicle mounted
Power supply	11-32 V DC
Display/keyboard location	Indicator console in cabin
Accuracy class	Y(b)

Software:

The software designation is 60364 and its version number is 1.xx, where xx changes when non-legally relevant modifications are added to the software

Interfaces:

- TXDR: Amphenol 7 way interface for pressure transducers
- PRINTER: JST 12 way interface for printer and data module
- PWR/CTRL: JST 15 way interface for power supply inputs as well as trigger, location sensors and inclinometer.

Alternatives:

Having a modified software. The software designation is 60364 and its version number is 2.xx, where xx changes when non-legally relevant modifications are made to the software. This software provides facilities to use MMS reporting software using data module and wireless communication, which shall not be used for legal purposes.

Having a modified instrument, designated the Express and Force, with reduced (Express) and no (Force) data handling functionality, and reduced keypads.

The software designation for the Express is 60395 and its version is 2.xx, where xx changes when non-legally relevant modifications are made to the software.

The software designation for the Force is 60408 and its version is 2.xx, where xx changes when non-legally relevant modifications are made to the software.

These models may be used with the Loadrite AAA-20709 inclinometer instead of the LR966 inclinometer. It is set to activate for a tilt greater than 6°.

Having the instrument designated the L2150, with modified indicator console layout and dedicated key for entering target weights.

The software designation for the L2150 is 60439 and its version is 1.xx, where xx changes when non-legally relevant modifications are made to the software.

This model may be used with the Loadrite AAA-20709 inclinometer instead of the LR966 inclinometer. It is set to activate for a tilt greater than 6°.

Certificate History

ISSUE NO.	DATE	DESCRIPTION
R51/2006-GB1-13.01	19 March 2013	Certificate first issued
-	-	No revisions have been issued.