OlML Certificate No. R60/2000-CN1-06.02

OIML CERTIFICATE OF CONFORMITY

Issuing authority

Name: Office of OIML Affairs, General Administration of Quality Supervision, Inspection and Quarantine Address: N0.9 Madiandonglu, Haidian District, Beijing, 100088China

Applicant

Name: Zhonghang Electronic Measuring Instrument CO.,LTD

Address: P.O.Box2, hanzhong 723007, ShaanXi, China

Manufacturer of the certified type (if the manufacturer is not the applicant)

Name:

Address:

Identification of the certified type

Model designation	B3G
Accuracy class	C3
Maximum capacity(Emax) —	50 kg,100 kg,250 kg,500kg
	1t,2.5t,5t,7.5t,10t
Ratio of minimum LC verification	6000,7500,10000, 12000 or 15000
interval Y=Emax/Vmin	
Minimum dead load (Emin)	0kg
Maximum number of load cell	3000
interval (n _{max})	
Apportionment factor(PLC)	0.7
Safe overload	150% Emax
Compensating Temperature range	-10 ~ +40

The numbers of the associated test reports and the included pages: 2004-WJ-0049 18 pages , 2004-WJ-0050 17 pages , 2005-WJ-0031 17 pages

OlML Certificate No. R60/2000-CN1-06.02

This certificate attests the conformity of the above-mentioned type(represented by the samples identified in the associated test report) with the requirements of the following Recommendation(s) of the International Organization of Legal Metrology (OIML).

 R:
 60

 Edition:
 2000

For accuracy class (if applicable): C3

This certificate relates only to the metrological and technical characteristics of the type of the instrument concerned ,as covered by the relevant OIML International Recommendation(s). This certificate does not bestow any form of legal international approval. The conformity was established by tests described in the associated test reports.



The CIML member



March 28, 2006

Important note:Apart from the mention of the certificate's reference number and the name of the OIML Member State in which the certificate was issued,partial quotation of the certificate or of the associated test report is not permitted,though they may be reproduced in full.