

# Physikalisch-Technische Bundesanstalt

Braunschweig und Berlin

Member State of OIML  
Germany



OIML Certificate N°  
**R76/1992-DE1-06.07**

## OIML CERTIFICATE OF CONFORMITY

### Issuing Authority

Name: Physikalisch-Technische Bundesanstalt  
Address: Bundesallee 100, 38116 Braunschweig  
Person responsible: Dr. Panagiotis Zervos

### Applicant

Name: Bizerba GmbH & Co. KG  
Address: Wilhelm-Kraut-Str. 65, 72336 Balingen

Manufacturer of the certified type is the applicant.

### Identification of the certified type

Nonautomatic, electromechanical, pricecomputing weighing instrument

Type: GLP-W...

Further characteristics see page 2

This Certificate attests the conformity of the above identified type (represented by the sample or samples identified in the associated Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

**R76-1**, edition 1992, including Amendment 1 (1994),  
for accuracy class **III**

This Certificate relates only to the metrological and technical characteristics of the type of instrument covered by the relevant OIML Recommendation identified above.

This Certificate does not bestow any form of legal international approval.

# Physikalisch-Technische Bundesanstalt

OIML Certificate N°  
**R76/1992-DE1-06.07**

The conformity was established by tests described in the Report N° 1.12-4023377 (12 pages) and the associated Test Reports N° 1.12-4023377/1 (51 pages), 1.12-4023377/2 (13 pages) and 1.12-4023377/3 (33 pages).

## The Issuing Authority

Dr. P. Zervos  
Regierungsdirektor

25.01.2007

## The OIML Member

Dr. R. Schwartz  
Direktor und Professor

25.01.2007

### Identification of the pattern (continued)

The weighing instrument consists of an indicator, comprising a microprocessor-system for further signal processing and control of the balance operation with thermal printer, LC-display, indicating weight with price, tare values and additional information and of a weighing module, comprising the load receptor and the strain gauge load cell. The A/D converter for signal processing may be incorporated either in the indicator or in the weighing module.

The weighing ranges with Max, Min, e, d and number of verification scale intervals may be chosen within the limits of No. 3.2 of R 76-1 and of the table 1.

Table 1

Accuracy class	III
Max	300 kg
$n \leq$ <sup>1)</sup>	6000
$n_i \leq$ <sup>2)</sup>	3000
Tare balancing range	100% of Max
Preset tare range	100% of Max <sup>1)</sup> 100% of Max <sub>1</sub> <sup>2)</sup>
Temperature range	-10°C / +40°C

<sup>1)</sup> This applies to each weighing range of single and multiple range instruments

<sup>2)</sup> This applies only to multi-interval instruments

**Important note:** Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate is issued, partial quotation of the Certificate and of the associated Test Report(s) is not permitted, although either may be reproduced in full.