



Member State of OIML United Kingdom of Great Britain and Northern Ireland

OIML Certificate No R76/1992-GB1-15.02

OIML CERTIFICATE OF CONFORMITY

Issuing authority:	National Measurement Office
Person responsible:	Paul Dixon – Director, Product Certification
Applicant:	CAS Corporation #262, Geurugogae-ro Gwangjeok-myeon Yangju-si Gyeonggi-do Republic of Korea
Manufacturor	The applicant

Manufacturer:

i ne applicant

Identification of the certified pattern:

CL7200 Series

This certificate attests the conformity of the above-mentioned pattern (represented by the samples identified in the associated test report) with the requirements of the following Recommendation of the International Organisation of Legal Metrology (OIML):

OIML R 76 - Edition 1992(E) for accuracy class: [III]

This certificate relates only to the metrological and technical characteristics of the pattern of the instrument concerned, as covered by the relevant OIML International Recommendation.

This certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the certificates reference number and the name of the OIML Member State in which the certificate was issued, partial quotation of the certificate or of the associated test report is not permitted, though they may be reproduced in full.

Issue Date: **Reference No:** 26 March 2015 TS1201/0121

Signatory: G Stones for Chief Executive National Measurement Office | Stanton Avenue | Teddington | TW11 0JZ | United Kingdom Tel +44 (0)20 8943 7272 | Fax +44 (0)20 8943 7270 | Web www.gov.uk/nmo

NMO is an Executive Agency of the Department for Business, Innovation & Skills



National Measurement Office

Page 1 This certificate includes 4 pages

The conformity was established by tests described in the associated pattern evaluation report P01500 which includes 13 pages.

Characteristics of the instrument:

This family of instruments is designated the CL7200 Series, and comprises the CL7200-U model. The instruments are Class III, mains-operated, self-indicating, price-computing, single or dual-interval, non-automatic weighing instruments. The instruments are designed for direct sales to the public.

Construction:

- Plastic construction
- Operator's keypad
- Stainless steel load receptor
- Operator front touch screen display and customer rear LCD display
- Level indicator
- Integrated printer

Devices:

- Initial zero setting device ($\leq 20\%$ of Max)
- Semi-automatic zero setting device ($\leq 4\%$ of Max)
- Zero tracking device ($\leq 4\%$ of Max)
- Automatic zero setting device ($\leq 4\%$ of Max)
- Zero indicator
- Net indicator
- Stable weight indicator
- Semi-automatic subtractive tare balancing device
- Preset tare
- Gravity compensation
- Price-computing
- Totalisation (including non-weighed items)
- PLU
- Fixed weight labelling
- Multi-vendor operation
- Calibration / set-up mode via sealed internal switch
- Self-service operation
- Modular display (with fixed legally relevant areas)

Interfaces:

- RS232C
- Cash drawer
- Ethernet
- Wireless LAN
- USB
- CAS Wi-Fi Module, model GWF-3M08

Load cell:

The load cell is a CAS load cell, model TPN, capacities (E_{max}) as per following table.

Technical data:

Model		CL7200-U				
Max	3/6 kg	6 kg	6/15 kg	15 kg	15/30 kg	30 kg
Min	20 g	40 g	40 g	100 g	100 g	200 g
e =	1/2 g	2 g	2/5 g	5 g	5/10 g	10 g
T≤	-2.999 kg	-2.998 kg	-5.998 kg	-5.995 kg	-9.995 kg	-14.99 kg
E _{max}	6 kg	6 kg	15 kg	15 kg	30 kg	30 kg

Note: E_{max} in the above table refers to the actual measuring range and does not include the dead load for the instrument.

The temperature range for the instruments is -10 °C / +40 °C.

The instruments operate on a 110 to 240 Vac (50/60 Hz) mains power supply.

Software identification:

The software is designated V3.xx.x, with xx.x reflecting minor, non-legally relevant modifications. This information is displayed at power up.

Software download using the communication ports is only possible via the USB interface, and is protected by switches on the sealed main board.

Sealing measures:

Access to the load cell, electronics, calibration and software download switches is prevented by wire-and seal or tamper evident label.

Alternatives manufacturers:

Shanghai CAS Electronics Co., Ltd, Maixinroad 448, Xinqiaozhen, Songjiangqu, Shanghai, China

CAS Elektronik San. Tic. A.S. Yukari Dudulu, Bostanci Cad. Mevdudi Sokak No: 34 Umraniye-Istanbul / Turkey

CAS (Zhejiang) Electronics Co., Ltd 99# Changjiang Road Jiashan County Zhejiang Province China

Certificate History

ISSUE NO.	DATE	DESCRIPTION
R76/1992-GB1-15.02	26 March 2015	Certificate first issued.
-	-	No revisions have been issued.