

## OIML Certificate of Conformity

**OIML Member State** The Netherlands Number R76/2006-NL1-14.16 Project number 14200153 Page 1 of 2

Issuing authority	NMi Certin B.V. Person responsible: C. Oosterman
Applicant and Manufacturer	Shanghai Teraoka Electronics Co., Ltd. Ting Lin Industry Developmental Zone Jin Shan District Shanghai 201505 China
Identification of the certified type	A Non-automatic weighing instrument Type : SM-120
Characteristics	See next page
identified in the OIML	the conformity of the above identified Type (represented by the sample(s) Test Report) with the requirements of the following Recommendation of the tion of Legal Metrology (OIML):
	OIML R 76 - Edition 2006 for accuracy class III
instrument covered by This Certificate does no Important note: Apart	only to the metrological and technical characteristics of the type of measuring the relevant OIML International Recommendation above-identified. t bestow any form of legal international approval. from the mention of the Certificate's reference number and the name of the which the Certificate was issued, partial quotation of the Certificate and of
	st Report(s) is not permitted, although either may be reproduced in full.
Issuing Authority	NMi Certin B.V., OIML Issuing Authority NL1 27 May 2014 C. Oosterman
* * * * * * * *	Head Certification Board
NMi Certin B.V. Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T +31 78 6332332 certin@nmi.nl www.nmi.nl	This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability. The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org



## OIML Certificate of Conformity

**OIML Member State** The Netherlands Number R76/2006-NL1-14.16 Project number 14200153 Page 2 of 2

haracteristics of the non-automatic weigh	ning instrument:
Accuracy class	
Maximum capacity	$3 \text{ kg} \le \text{Max} \le 30 \text{ kg}$
/erification scale interval	+ + + + + + + e ≥ 1 g + + + + + +
Neighing range(s)	Single interval Multi-interval
Maximum number of scale intervals	n ≤ 6000 divisions
Maximum number of scale intervals multi-interval)	$n \le 3000$ divisions (per partial weighing range)
Maximum number of partial weighing ranges	2
Tare + + + + + + + + + + + + + + + + + + +	T $\leq$ -50% for instruments with one weighing range T $\leq$ -Max <sub>1</sub> for multi-interval instruments
lemperature range	-10 °C / +40 °C
Power supply voltage	220 V / 230 V / 240 V AC 50/60 Hz
Application	Intended to be used for direct sales to the public
oftware identification	Version number: V01.xx <sup>(1)</sup> Checksum: B19F <sup>(2)</sup>
<sup>)</sup> where 01 represents the legally relevant part a epresents the non-legally relevant software.	and xx is a number between 00 and 99, which
for legally relevant part.	