OIML Certificate of Conformity

OIML Member State
The Netherlands

Number R76/2006-NL1-14.58
Project number 14200417

Issuing authority	NMi Certin B.V. Person responsible: C. Oosterman
Applicant and Manufacturer	Mettler-Toledo, LLC 1150 Dearborn Drive Worthington, Ohio 43085-6712 United States of America
Identification of the certified type	A **Non-automatic weighing instrument** Type : BC Series
Characteristics	See next page

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 76 - Edition 2006 for accuracy class (III)

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified.
This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority

NMi Certin B.V., OIML Issuing Authority NL1
11 November 2014

C. Oosterman
Head Certification Board

NMi Certin B.V.
Hugo de Grootplein 1
3314 EG Dordrecht
the Netherlands
T +31 78 6332332
certin@nmi.nl
www.nmi.nl

OIML Certificate of Conformity

OIML Member State
The Netherlands

Number R76/2006-NL1-14.58
Project number 14200417

The conformity was established by the results of tests and examinations provided in the associated OIML Test Report(s):
- No. NMi-14200417-01 dated 16 October 2014 that includes 29 pages;
- No. NMi-14200417-02 dated 16 October 2014 that includes 29 pages.

Characteristics of the non-automatic weighing instrument:

Non-automatic weighing instrument		MT1260	0795	SLP331D
Accuracy class		(III)		
Maximum capacity		Max ≤ 150 kg	Max ≤ 150 kg	30 ≤ Max ≤ 50 kg
Verification scale interval		e ≥ 0,05 kg	e ≥ 0,02 kg	e ≥ 0,001 kg
Weighing range(s)		Single interval	Single interval Multiple range	Single interval Multi-interval Multiple range
Maximum number of scale intervals (one weighing range)		n ≤ 3000 divisions	n ≤ 3000 divisions	n ≤ 3500 divisions
Maximum number of scale intervals (multi-interval)				n ≤ 3500 divisions (per partial weighing range)
Maximum number of partial weighing ranges		1	2	3
Maximum number of scale intervals (multiple range)			n ≤ 3000 divisions (per weighing range)	n ≤ 3500 divisions (per weighing range)
Maximum number of weighing ranges		1	2	3
Tare		T ≤ -Max		
Temperature range		0 °C / 40 °C	0 °C / 40 °C	0 °C / 40 °C
Power supply voltage		5 V DC (USB)		
Application		Intended to be used for determining a transport tariff Intended to be used for direct sales to the public		
Software identification	Version	0.00.xxxx Where xxxx is a number between 0000 and 9999 which represents the non legally relevant part of the software		
	Checksum (CRC32)	0x93B46AB4	0x805D6909	0x9187A86A