

OIML Certificate of Conformity

OIML Member State The Netherlands Number R76/2006-NL1-15.26 Project number 15200070 Page 1 of 2

Issuing authority	NMi Certin B.V. Person responsible: C. Oosterman	
Applicant and Manufacturer	Dräger Medical Systems, Inc. 3135 Quarry Road Telford, PA 18969 United States of America	
ldentification of the certified type	A Non-automatic weighing instrument Type : Resuscitaire Radiant Warmer (RW82, RW82-VHA) Resuscitaire Birthing Room Warmer (WBR82)	
Characteristics	See next page	
+ identified in the OIML	the conformity of the above identified Type (represented by the sample(s) Test Report) with the requirements of the following Recommendation of the tion of Legal Metrology (OIML):	
	OIML R 76 - Edition 2006 for accuracy class III	
instrument covered by	only to the metrological and technical characteristics of the type of measuring the relevant OIML International Recommendation above-identified. It bestow any form of legal international approval.	
OIML Member State in	from the mention of the Certificate's reference number and the name of the which the Certificate was issued, partial quotation of the Certificate and of st Report(s) is not permitted, although either may be reproduced in full.	
Issuing Authority	NMi Certin B.V., OIML Issuing Authority NL1	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	10 September 2015 C. Oosterman Head Certification Board	
NMi Certin B.V. Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T +31 78 6332332 certin@nmi.nl www.nmi.nl	This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability. The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org	



OIML Certificate of Conformity

OIML Member State The Netherlands Number R76/2006-NL1-15.26 Project number 15200070 Page 2 of 2

The conformity wa OIML Test Report: - No. NMi-15200 Characteristics o	0070-01 dated 10 9	Septemb	er 20	15 tha	at incl	udes	56 p	+ $+$	+ + + + + + + + + + + + + + + + + + + +	+++++++++++++++++++++++++++++++++++++++	+ +	+	+ + + + + + + + + + + + + + + + + + + +	
Accuracy class	* * * * * *	* *	+ +	+ + + +	+ + +	+ -	+ +		+ +	+	+ +	+	+ -	+ +
Maximum capacity	/ + + + + + + + + + + + + + + + + + + +	+ + +	+ +	+ +	+ +	+ + + + + + + + + + + + + + + + + + + +	Ma	ax ≤ 8	kg	+	+ +	+	+ •	+ -
Verification scale i	nterval + + +	+ +	+ +	+ +	+ +	+	e	≥ 10 g	9+ +	+	+ +	• +	+ -	+
Weighing range	+ + + + + + + + + + + + + + + + + + +	+ + -	+ +	+ +	+ +	+	Sing	le inte	rval	+	+ +	• +	+ -	÷
Maximum number	[•] of scale intervals	+ + +	+ +	+ + +	* *	‡ !	n ≤ 8(00 divi	sions	+++++++++++++++++++++++++++++++++++++++	* *	+	+ -	+ +
Tare + +	* * * * * *	+ +	+ +	+ +	+ +	+	Ť	≤ -4 k	g * +	+	+ +	+	+ -	t
Temperature rang	e+ + + + + +	+ +	+ +	* *	++	+	+10	°C / +4	0 °C	+	+ +	• +	+ -	+
Power supply volta	* * * * * * * * * * * * * * * * * * *	+ + +	+ +	12 V	′ DC t			n AC/D V AC			supp	ly of	+ -	+
Application	+ + + + + + +	+ +	+ +	+ +T	o be i	used	only	for we	eighin	g p	atien	ts 🗕	+ -	÷
Software identifica	ation	+ + +	+ +	* *	* *	Ve	rsion	numb	er: 1.0)8	* *	• •	+ - + -	+
+ + + + + +	+ + + + + +	+ +	+ +	+ +	+ +	+	+ +	+ +	+ +	÷	+ +	+	+ -	÷