

OIML Certificate of Conformity

OIML Member State

The Netherlands

Number R76/2006-NL1-15.44 Project number 15200539 Page 1 of 2

NMi Certin B.V. Issuing authority

Person responsible: C. Ooste

Applicant and Manufacturer

BISON Group Ltd Unit 2, 11 Wharf Street

Dunedin 9016 New Zealand

Identification of the

An Indicator

certified type

Type Container Weighing System

Characteristics See next page

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 76 - Edition 2006 for accuracy class (III)



This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

NMi Certin B.V., OIML Issuing Authority

5 December 2016

NMi Certin B V Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T +31 78 6332332 certin@nmi.nl www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org







OIML Certificate of Conformity

OIML Member State The Netherlands

Number R76/2006-NL1-15.44 Project number 15200539 Page 2 of 2

The conformity was established by the results of tests and examinations provided in the associated OIML Test Report(s):

- No. NMi-15200539-01 dated 30 November 2016 that includes 42 pages.

Characteristics of the indicator:

Accuracy class	
Weighing range(s)	Single interval
Maximum number of scale intervals + + + + + +	n ≤ 1000 divisions
Load cell excitation voltage	* * * * * 5 V DC
Minimum input voltage per verification scale interval	10 μV
Minimum load cell resistance	350 Ω
Maximum load cell resistance + + + + + + + +	+ + + + + 2100 Ω + + + + + +
Fraction of the maximum permissible error	+ + + + + + 0,5 + + + + + + +
Load cell connection	6-wire
Maximum value of the cable length per cross wire section between the indicator and the load cells	The load cells are connected directly without junction box
Temperature range	-10 °C / +40 °C
Power supply voltage	6 V DC
Software identification	Version number: 4.07.xx (xx is a number between 00 and 99)