

OIML Certificate of Conformity

OIML Member State The Netherlands Number R76/2006-NL1-16.10 Project number 15200619 Page 1 of 2

Issuing authority	NMi Certin B.V. Person responsible: C. Oosterman	
Applicant and Manufacturer	Mettler-Toledo GmbH Im Langacher 44 8606 Greifensee Switzerland	
Identification of the certified type	A Non-automatic weighing instrument Type : FreshBase or FB	
Characteristics	See next page	
identified in the OIML	the conformity of the above identified Type (represented by the sample(s) Test Report) with the requirements of the following Recommendation of the tion of Legal Metrology (OIML):	
	OIML R 76 - Edition 2006 for accuracy class (III)	
instrument covered by	only to the metrological and technical characteristics of the type of measuring the relevant OIML International Recommendation above-identified. ot bestow any form of legal international approval.	
OIML Member State in	from the mention of the Certificate's reference number and the name of the which the Certificate was issued, partial quotation of the Certificate and of est Report(s) is not permitted, although either may be reproduced in full.	
Issuing Authority	NMi Certin B.V., OIML Issuing Authority NL1 + + + + + + + + + + +	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	18 May 2016 C. Oosterman Head Certification Board	
NMi Certin B.V. Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T +31 78 6332332 certin@nmi.nl www.nmi.nl	This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability. The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org	



OIML Certificate of Conformity

OIML Member State The Netherlands Number R76/2006-NL1-16.10 Project number 15200619 Page 2 of 2

	eighing instrument:
Accuracy class	
Maximum capacity	6 kg ≤ Max ≤ 30 kg
Verification scale interval	e ≥ 1 g
Weighing ranges	Single interval Multi-interval
Maximum number of scale intervals (one weighing range)	n ≤ 3000 divisions
Maximum number of scale intervals (multi-interval)	n ≤ 3000 divisions (per partial weighing range)
Maximum number of partial weighing ranges	2
Tare + + + + + + + + + + + + + + + + + + +	$T \leq$ -100% for instruments with one weighing range $T \leq$ -Max_1 for multi-interval instruments
Temperature range	-10 °C / +40 °C
Power supply voltage	100 – 240 V AC 50/60 Hz
Application	Intended to be used for direct sales to the public
Software identification	Name Version number
· · · · · · · · · · · · · · · · · · ·	MT UPOS Scale 1.x.y (x.y = 0999)