

OIML Certificate of Conformity

OIML Member State The Netherlands Number R76/2006-NL1-16.34 Project number 15200721 Page 1 of 2

NMi Certin B.V. Issuing authority Person responsible: C. Ooster Mettler-Toledo GmbH Applicant and Manufacturer Im Langacher 44 8606 Greifensee Switzerland Identification of the A Non-automatic weighing instrument certified type Type bPlus Characteristics See next page This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML): OIML R 76 - Edition 2006 for accuracy class (III) This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval. Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full. NMi Certin B.V., OIML Issuing Authority Issuina 8 Jul/ 2016 Softerman Head Certification Boar NMi Certin B V This document is issued under the Parties concerned can Hugo de Grootplein 1 provision that no liability is lodge objection against 3314 EG Dordrecht accepted and that the applicant this decision, within six the Netherlands shall indemnify third-party liability. weeks after the date of T+31 78 6332332 submission, to the The notification of NMi Certin B.V. general manager of NMi certin@nmi.nl as Issuing Authority can be verified www.nmi.nl (see www.nmi.nl). at www.oiml.org



OIML Certificate of Conformity

OIML Member State The Netherlands Number R76/2006-NL1-16.34 Project number 15200721 Page 2 of 2

 No. NMi-15200721-02 dated 8 July 2016 t Characteristics of the non-automatic we 	
Accuracy class	
Maximum capacity	3 kg ≤ Max ≤ 30 kg
Verification scale interval	e ≥ 1 g
Weighing ranges	Single interval Multi-interval
Maximum number of scale intervals (one weighing range)	n ≤ 3000 divisions
Maximum number of scale intervals (multi-interval)	n ≤ 3000 divisions (per partial weighing range)
Maximum number of partial weighing ranges	
Tare * * * * * * * * * * * * * *	T ≤ -Max
Temperature range	-10 °C / +40 °C
Power supply voltage	100 – 240 V AC 50/60 Hz
Application + + + + + + + + +	Intended to be used for direct sales to the public
Software identification	where "xxx" represents the legally non-relevant software part and "yyy" represents bug fixes