

OIML Certificate of Conformity

OIML Member State The Netherlands Number R76/2006-NL1-16.53 Project number 15200788 Page 1 of 2

 Issuing authority 	NMi Certin B.V. Person responsible: C. Oosterman	
Applicant and Manufacturer	Xiamen Rongta Technology Co., Ltd. 3F/E Building, Gaoqi Industrial Area, Gaoqi Beisan Road, Dianqian Huli Xiamen City Peoples Republic of China	
Identification of the	A Non-automatic weighing instrument	
certified type		0, RLS1100,
		0A, RLS1100A
Characteristics	See next page	
+ identified in the OIML	the conformity of the above identified Type (repro Test Report) with the requirements of the followin ation of Legal Metrology (OIML):	
	OIML R 76 - Edition 2006 for accuracy class (III)	
⁺ instrument covered by	only to the metrological and technical characteris the relevant OIML International Recommendation ot bestow any form of legal international approva	n above-identified.
OIML Member State in	from the mention of the Certificate's reference nu which the Certificate was issued, partial quotation est Report(s) is not permitted, although either may	n of the Certificate and of
+ + + + + + + + + + + + + + + + + + +		* * * * * * * * * * * *
Issuing Authority	NMi Certin B.V., OIML Issuing Authority NL1 15 November 2016 C. Oosterman Head Certification Board	$\begin{array}{c} + + + + + + + + + + + + + + + + + + +$
NMi Certin B.V. Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T +31 78 6332332 certin@nmi.nl www.nmi.nl	This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability. The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org	PROFILE ARRANGE



OIML Certificate of Conformity

OIML Member State The Netherlands Number R76/2006-NL1-16.53 Project number 15200788 Page 2 of 2

Characteristics of the non-automatic w	eighing instrument:		
Accuracy class			
Maximum capacity	6 kg ≤ Max ≤ 30 kg		
Verification scale interval	+ + + + + + + + + + + + + + + + + + +		
Weighing ranges	Single interval Multi-interval		
Maximum number of scale intervals (one weighing range)	n ≤ 3000 divisions		
Maximum number of scale intervals (multi-interval)	n ≤ 3000 divisions (per partial weighing range)		
Maximum number of partial weighing ranges	· · · · · · · · · · · · · · · · · · ·		
Tare + + + + + + + + + + + + + + + + + + +	T \leq -50% for instruments with one weighing range T \leq -Max ₁ for multi-interval instruments		
Temperature range	0 °C / +40 °C		
Power supply voltage	110 – 240 V AC 50/60 Hz		
Application + + + + + + + + +	+ + Intended to be used for direct sales to the public		
Software identification	Version number: V1.xxx (x = 0 999) Checksum: D735A750		
* * * * * * * * * * * * * *	* * * * * * * * * * * * * * * * * * * *		