

DRAFT
RECOMMENDATION

TC 7
(UK)

SUBMITTED
FOR DIRECT
CIML ONLINE
APPROVAL

New Draft Recommendation: R 35-3

Material measures of length for general use.

Part 3: Test report format

*Draft submitted for direct CIML online approval
on 2011.01.18.*

Voting closes on 2011.04.18



Contents

<i>Explanatory note</i>	3
<i>Foreword</i>	4
<i>Explanatory notes to the Test Report Format</i>	5
I Type evaluation report	7
1 Information concerning the type	7
1.1 General	7
1.2 Model submitted	7
1.3 Material measures of length (complete)	8
1.4 Separate blade	9
1.5 Separate case	9
1.6 Separate sinker	10
1.7 Supplementary readout/display	10
1.8 Supplementary electronic sensing device	11
1.9 Identification	12
2 Documents concerning the type	13
3 General information concerning the test equipment	13
4 General information concerning simulators	13
5 Checklist for measures of length examinations and performance tests	14
5.1 Checklist for external examinations	14
5.2 Checklist for accuracy tests	29
5.3 Checklist for influence factor and disturbance tests for electronic devices	30
6 Type evaluation tests (for all measures of length)	32
6.1 Datasheet for blade accuracy calculations	32
6.2 Scale accuracy and large scale linearity	33
6.3 Scale interval accuracy	34
6.4 Scale interval linearity	35
6.5 Accuracy of other metrological components	35
6.6 Indicating devices	37
7 Tests for influence factors and disturbances	39
7.1 Static temperatures (specified high)	39
7.2 Static temperatures (specified low)	40
7.3 Damp heat, cyclic (condensing)	41
7.4 Mechanical shock	42
7.5 Radio-frequency immunity	43
7.6 Electrostatic discharge	46
7.7 Voltage of battery power source	47

II Initial verification report	49
1 Information concerning the EUT verified	49
2 Initial Verification Test Report.....	50
2.1 Example 1: Approved measure – no additional electronic devices	50
2.2 Example 2: Approved measure – with additional electronic devices	52
Annex A (Mandatory) – List of documents received from the manufacturer	55
Annex B (Mandatory) – List of test equipment used in examinations and tests	56
Annex C (Mandatory, when applicable) – List of simulators used in examinations and tests	57

Explanatory Note

The present version of the International document OIML R35 dates back from 1985.

In June 1999 the United Kingdom, which holds the TC 7 Secretariat, proposed to initiate a review and revision of R35 and to undertake this work as a project for TC 7. The secretariat proposed that Part 2 (Test methods) and Part 3 (Test report format) of OIML R35 would be undertaken as a separate project once the scope of Part 1 (Metrological and technical requirements) had been finalised.

Part 2 -1CD and Part 3 -1CD were issued in May 2006 with Part 1 5CD. Following a few additional amendments Part 1-1DR was approved by CIML in October 2007.

This document is the first revision of the Draft Recommendation of Part 3 following receipt of members' comments on 2CD in 2008 and the correction of minor errors.

Foreword

The International Organization of Legal Metrology (OIML) is a worldwide, intergovernmental organization whose primary aim is to harmonize the regulations and metrological controls applied by the national metrological services, or related organizations, of its Member States.

The two main categories of OIML publications are:

- **International Recommendations (OIML R)**, which are model regulations that establish the metrological characteristics required of certain measuring instruments and which specify methods and equipment for checking their conformity; the OIML Member States shall implement these Recommendations to the greatest possible extent;
- **International Documents (OIML D)**, which are informative in nature and intended to improve the work of the metrological services.

OIML Draft Recommendations and Documents are developed by technical committees or subcommittees which are formed by the Member States. Certain international and regional institutions also participate on a consultation basis.

Cooperative agreements are established between OIML and certain institutions, such as ISO and IEC, with the objective of avoiding contradictory requirements; consequently, manufacturers and users of measuring instruments, test laboratories, etc. may apply simultaneously OIML publications and those of other institutions.

International Recommendations and Inter-national Documents are published in French (F) and English (E) and are subject to periodic revision.

This publication – reference OIML R 35-3, edition 200x (E) – was developed by the OIML subcommittee TC 7 *Measuring instruments for length and associated quantities*. It was approved for final publication by the International Committee of Legal Metrology in 20xx.

OIML Publications may be downloaded from the OIML web site in the form of PDF files. Additional information on OIML Publications may be obtained from the Organization's headquarters:

Bureau International de Métrologie Légale
11, rue Turgot - 75009 Paris - France
Telephone: 33 (0)1 48 78 12 82 and 42 85 27 11
Fax: 33 (0)1 42 82 17 27
E-mail: biml@oiml.org
Internet: www.oiml.org

Material measures of length for general use

Part 3 Test Report Format

Explanatory notes to the Test Report Format

Implementation of this Test Report Format is informative with regard to the implementation of R 35-1 and R 35-2 in national regulations; however, **its implementation is mandatory within the framework of the OIML Certificate System for Measuring Instruments** [R 35-2, 9].

Section I shows the required format of a Type Evaluation Report for a measures of length.

A Type Evaluation Report for a dimensioned case or electronic sensing device requires a similar format. However, some modifications to the tables may be required because a large number of variations in the design of these separable units is possible.

Some examples of tables for presenting the test results for measures and ancillary devices are shown in Section II for Initial Verification Reports. These tables may also be adapted for Type Evaluation Reports.

Meaning of symbols:

/ Indication

EUT Equipment under test

mpe Maximum permissible error

For each examination and test the checklist shall be completed according to this example:

For each test, the "SUMMARY OF TYPE EVALUATION" and the "CHECKLIST" shall be completed according to this example:

when the instrument has passed the test:

when the instrument has failed the test:

when the test is not applicable:

P	F	P = Passed F = Failed
X		
	X	
/	/	

The white spaces in boxes in the headings of the report should always be filled according to the following example:

	At start	At end	
Temp.:	20.5	21.1	°C
Rel h.:			%
Date:	2006-05-20	2006-05-21	yyyy-mm-dd
Time:	16:00:05	16:30:25	hh:mm:ss

where:

Temp. = temperature

Rel.h = relative humidity

"Date" in the test reports refers to the date on which the test was performed.

I. Type Evaluation Report

1. Information concerning the type

1.1 General

Application number:

Applicant:

Authorized representative:

Address:

.....

.....

.....

Testing laboratory:

Address:

.....

.....

.....

1.2 Model submitted

New model:

.....

.....

Variant of approved model (details):

.....

.....

Approval number:

Table 1 Model submitted

Submitted for approval tests	Yes*	No*	Remarks
Material measure of length (complete)			
Separate blade			
Separate case			
Separate sinker			
Supplementary readout/display (permanently attached to measure)			
Supplementary electronic sensing device (permanently attached to measure)			

* Tick (X) as appropriate

1.3 Material measure of length (complete)

Manufacturer:

Model number:

Type details:

Category (R 35-2, 7.1.a):

Sub-category (R 35-2, 7.1.b):

Blade material:

Accuracy class (R 35-1, 4.1):

Nominal length: m

Blade width: mm

Scale interval: mm

If applicable:

Maximum admissible temperature: °C

Environmental class (R 35-1, 27.4):

Mechanical environment (R 35-2, 6.2.7):

Electromagnetic environment (R 35-2, 8.4):

Installation details:

Tension: N

Other relevant information:

Coefficient of thermal expansion: 10^{-6} per °C

Internal impedance of specified power source: ohm

Additional:

1.4 Separate blade

Manufacturer:

Model number:

Type details:

Category (R 35-2, 7.1.a):

Sub-category (R 35-2, 7.1.b):

Blade material:

Accuracy class (R 35-1, 4.1):

Nominal length: m

Blade width: mm

Scale interval: mm

Installation details:

Tension: N

Other relevant information:

Coefficient of thermal expansion: 10^{-6} per °C

Additional:

Approval nos. of compatible blades:

1.5 Separate case

Manufacturer:

Model number:

Type details:

Category (R 35-2, 7.1.a):

Accuracy class (R 35-1, 4.1):

Blade nominal length: m

Blade width: mm

Case dimensions: mm

Installation details:

Approval nos. of compatible blades:

1.6 Separate sinker

Manufacturer:

Model number:

Type details:

Category (R 35-2, 7.1.a):

Sinker material:

Accuracy class (R 35-1, 4.1):

Blade nominal length: m

Blade width: mm

Sinker length: mm

Sinker mass: gm

Thermal coefficient of linear expansion: 10^{-6} per °C

Installation details:

Approval nos. of compatible blades:

1.7 Supplementary readout/display

Manufacturer:

Model number:

Type details of compatible blades:

Category (R 35-2, 7.1.a):

Accuracy class (R 35-1, 4.1):

Nominal length: m

Scale interval: mm

Approval nos. of compatible blades:

Power source:

Type (battery, solar, etc.):

U_{\max} : V

U_{\min} : V

Internal impedance:ohm

Frequency (*if applicable*):.....Hz

Installation details (electrical):

Wiring instructions:

Mounting arrangement:

Orientation limitations

Maximum admissible temperature: °C

Environmental class (R 35-1, 27.4):

Mechanical environment (R 35-2, 6.2.7):

Electromagnetic environment (R 35-2, 8.4):

1.8 Supplementary electronic sensing device

Manufacturer:

Model number:

Type details of compatible blades:

Category (R 35-2, 7.1.a):

Sub-category (R 35-2, 7.1.b):

Accuracy class (R 35-1, 4.1):

Nominal length: m

Blade width: mm

Scale interval: mm

Approval nos. of compatible blades:

Power source:

Type (battery, solar, etc.):

U_{\max} : V

U_{\min} : V

Internal impedance: ohm

Frequency (*if applicable*): Hz

Installation details (electrical):

Wiring instructions:

Mounting arrangement:

Orientation limitations

Maximum admissible temperature: °C

Environmental class (R 35-1, 27.4):

Mechanical environment (R 35-2, 8.3):

Electromagnetic environment (R 35-2, 8.4):

1.9 Identification

Add any additional information pertaining to identification of the EUT:
(attach photograph here, if available)

2. Documents concerning the type (R35-2, 5)

Annex A provides a table on which to list the documents submitted by the manufacturer with the type for testing.

3. General information concerning the test equipment

Details of all items of measuring equipment and test instruments used for the type examinations and initial verifications shall be listed in Annex B, e.g. instruments for measuring

- Linear dimensions,
- Temperature,
- Voltage
- Signal generators (for pulse, current or voltage).

4. General information concerning simulators

Details of any simulators used for the type examinations and initial verifications shall be listed in Annex C:

5. Checklist for measures of length examinations and performance tests

5.1 Checklist for external examinations

Note: § (R 35-1) Refers to clause numbers in OIML R35-1 *Material measures of length*.
Part 2: Metrological and technical requirement Edition 200x (E).

5.1.1 External examination for all measures of length												
§ (R 35-1)	Requirement	P	F	Remarks								
5	Nominal length											
5.1	<div>The nominal length in column 1 shall be an integral multiple of the factor shown in column 2.</div> <table><tr><td>Nominal length m</td><td>Multiple of m</td></tr><tr><td>≤15</td><td>0.5</td></tr><tr><td>15 < L ≤ 100</td><td>5</td></tr><tr><td>>100</td><td>50</td></tr></table>	Nominal length m	Multiple of m	≤15	0.5	15 < L ≤ 100	5	>100	50			
Nominal length m	Multiple of m											
≤15	0.5											
15 < L ≤ 100	5											
>100	50											
5.2	Other values may be deemed appropriate for specific applications provided that the specific application is clearly indicated on the measure.											
5.3	Land surveying measures shall have nominal lengths of 5, 10, 20, 50, 100 or 200 metres.											
6	Materials											
6.1	The measures and their supplementary devices shall be made of materials which, under normal conditions of use, are sufficiently durable, stable and resistant to environmental influences.											
6.2	The variations in length due to temperature differences equal to 8°C above or below the reference temperature shall not exceed the maximum permissible errors for the accuracy class to which the measure belongs;											
6.2	A variation of ± 10 % of the specified tension shall not produce a variation in length exceeding the maximum permissible error.											
7	Construction											

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
7.1	The measures and their supplementary devices shall be well and robustly constructed and carefully finished.			
7.2	The dimensions and shape of the cross-section of measures shall be such that, under normal conditions of use, measurements can be made with the degree of accuracy required for the accuracy class to which the measures belong.			
7.3	Tape measures – when it is stretched out on a flat surface, the tape measure's edges shall be virtually straight and parallel.			
7.4	End measures – the surfaces forming the two principal scale marks (end surfaces) shall be flat and perpendicular to the longitudinal axis of the measure.			
7.5	End or composite measures made of wood or other material of durability equal to or less than that of wood – the end surfaces shall be provided with a bracket, plate or end fitting, which is resistant to wear and impact damage and is suitably attached to the measure.			
7.6	Supplementary devices shall not cause confusion and shall be designed and attached to the measure in such a way that, under normal conditions of use, it is virtually impossible for the measurement uncertainty to be increased.			
7.7	Tape measures – winding devices shall be made in such a way that they do not cause any permanent deformation of the tape.			
7.8	On certain types of measures, a blank length of the measure, extending beyond the principal scale mark at the end of the measure and long enough for verification purposes, may be provided.			
8	Scale			
8.1	The scale shall be clear, regular, indelible and carried out in such a way that reading is definite, easy and			

5.1.1 External examination for all measures of length																
§ (R 35-1)	Requirement	P	F	Remarks												
	unambiguous.															
8.2	The scale interval shall be of the form: $1 \times 10^n, 2 \times 10^n$ or 5×10^n metres, Where n is a positive or negative whole number or zero.															
8.2	For the nominal lengths shown in column 1, the scale interval shall not exceed the values shown in column 2. <table border="1"><thead><tr><th>Nominal length m</th><th>Maximum interval size</th></tr></thead><tbody><tr><td>0.5, 1.0</td><td>1 mm</td></tr><tr><td>$1.0 < L \leq 2$</td><td>1 cm</td></tr><tr><td>$2.0 < L < 10$</td><td>10 cm</td></tr><tr><td>$10.0 \leq L < 50$</td><td>20 cm</td></tr><tr><td>≥ 50</td><td>50 cm</td></tr></tbody></table> Note: These values may be exceeded for specific applications, provided the specific application is indicated on the measure.	Nominal length m	Maximum interval size	0.5, 1.0	1 mm	$1.0 < L \leq 2$	1 cm	$2.0 < L < 10$	10 cm	$10.0 \leq L < 50$	20 cm	≥ 50	50 cm			
Nominal length m	Maximum interval size															
0.5, 1.0	1 mm															
$1.0 < L \leq 2$	1 cm															
$2.0 < L < 10$	10 cm															
$10.0 \leq L < 50$	20 cm															
≥ 50	50 cm															
8.3	When the scale marks are lines:															
	a) They shall be straight, perpendicular to the axis of the measure, and all shall have the same width, which shall be constant throughout their length															
	b) The length of the lines shall be related to the corresponding unit of measurement. The lines shall be such that they form a distinct and clear scale and that their width shall not cause any measurement uncertainty.															
	c) The maximum admissible width of the lines shall not exceed the values given in Table1 of R35-2.															
8.4	Certain sections of the scale, particularly towards the ends, may be subdivided into decimal sub-multiples of the scale interval adopted for the															

5.1.1 External examination for all measures of length										
§ (R 35-1)	Requirement	P	F	Remarks						
	measure as a whole.									
8.4	The width of the lines may be less in the areas of reduced scale intervals than on the rest of the measure.									
8.5	Scale marks may also take other forms: <table border="1"><tr><td>Scale interval</td><td>Optional form of scale mark*</td></tr><tr><td>≥ 1 cm</td><td>Holes</td></tr><tr><td>≥ 1 dm</td><td>Other marks</td></tr></table> <p>* Provided that these marks ensure sufficiently precise reading, taking into account the accuracy class to which the measure belongs.</p>	Scale interval	Optional form of scale mark*	≥ 1 cm	Holes	≥ 1 dm	Other marks			
Scale interval	Optional form of scale mark*									
≥ 1 cm	Holes									
≥ 1 dm	Other marks									
8.6	A measure may have more than one scale, for which the scale intervals may be different.									
9	Numbering									
9.1	The numbering shall be clear, regular, indelible, and carried out in such a way that reading is definite, easy, and unambiguous									
9.2	The numbering sequence shall be fully sequential, or partially sequential and partially repetitive.									
9.2	In the case covered by 8.4 above, the numbering in parts with reduced scale intervals may be different from that for the rest of the measure.									
9.3	The position, dimensions, shape, colour and contrast of the numbers shall be appropriate to the scale and the associated scale marks.									
9.3	Depending on how the measure is to be read, the numbers shall be inscribed parallel or perpendicular to the edge of the measure.									
9.4	The numbers representing millimetres, centimetres, decimetres, or metres shall									

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
	not be accompanied by the corresponding symbols			
9.4	Only scale marks corresponding to complete metres may be numbered in metres, in which case these numbers shall be followed by the symbol “m”. The number of preceding metres may be repeated in the same way in front of the other numbered scale marks.			
9.4	Millimetre scales shall be numbered every centimetre.			
9.4	Line measures whose scale interval is in the form of 2×10^n and is not less than 2 cm - all scale marks shall be numbered.			
9.5	On a measure with several scales, the numbering of these scales may be different and the numbering systems may increase in the same direction or in the opposite direction.			
10	Inscriptions			
10.1	The following inscriptions are mandatory in all cases:			
	a) Nominal length (optional in a rectangle) (see 10.3 below);			
	b) The numeric code, trade mark or trade name of the manufacturer and/or of his representative;			
	c) The designation of accuracy class: I, II, or III in an oval;			
10.2	The following inscriptions are mandatory in certain cases:			
	a) The reference temperature, if other than 20 °C (see 10.3 below);			
	b) The tension, if specified (see 10.3 below);			
	c) The specific use for which the measure is intended, in the cases covered by R35-1, 5 (nominal length) and R35-1, 8.2 (scale interval).			
10.3	Nominal length, temperature, and tension shall be expressed in one of the			

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
	units specified in the OIML International Document D 2 “Legal units of measurement”, followed by the corresponding legal symbol.			
10.4	All of these inscriptions shall be clearly visible and readable, and placed at the beginning of the measure or on the case of the measure if the case and measure are not separable.			
10.5	Other non-metrological inscriptions specified in particular regulations or authorized by competent national authorities may appear on the measure.			
10.6	Advertising inscriptions may appear on the measures, provided the requirement of 10.7 is met.			
10.7	All inscriptions shall be arranged so that they do not interfere with the reading of the measure.			
10.8	Under the sole responsibility of the manufacturer, the thermal expansion coefficient of the material of which the measure is made, may be indicated in the form $\alpha = \dots/^{\circ}\text{C}$ or $\alpha = \dots \text{K}^{-1}$.			
11	Indicating device			
11.1.1	Indicating devices may be used only with semi-rigid steel tape measures with readout and with flexible steel tape measures with tensioning weight or sinker equipped with electronic sensing.			
11.1.2	The indicating device shall be in addition to the scale marks on the blade.			
11.1.2	The indicating device shall provide an easily read, reliable and unambiguous visual indication of the indicated length throughout the whole length of the measure.			
11.1.3	The indicating device shall display the indicated length up to and including the nominal length of the measure.			
11.1.4	The indicated length shall be expressed in metres (symbol m) or authorised multiples and sub-multiples and the appropriate symbol shall appear			

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
	immediately adjacent to the indicated length.			
11.1.5	The indicated length is given by a line of adjacent digits appearing in one or more apertures.			
11.1.5	- The advance of a given digit shall be completed while the digit of the next immediately lower decade changes from 9 to 0.			
11.1.6	The length displayed on the indicating device shall agree with the measurement made by the blade to the nearest scale interval of the blade.			
11.1.7	There shall be no ambiguity in distinguishing between the length currently being measured and alternative displays.			
11.2.2	On switch-on and optionally on demand, it shall be possible to visually check the correct operation of the entire display. This shall comprise: <ul style="list-style-type: none"> • displaying all the elements (“eights” test); • blanking all the elements (“blank” test); • displaying “zeros” (“zeros” test). Each step of the sequence shall last at least 0.5 s.			
13	Verification (or control) marks			
	Measures shall be constructed so that they can accommodate the verification (or control) marks prescribed by national regulations; a space shall be provided for this purpose near the beginning of the measure.			
	A — MEASURES FOR SHORT LENGTHS			
14	Semi-rigid steel tape measures in a case			
14.1	These measures shall have nominal lengths between 0.5 and 15 metres. See 5.1 & 5.2 also.			
14.1	They shall be of the end, line, or composite type.			
14.2.1	If the zero end is of a squared end type and is fitted with a ring, this ring may			

5.1.1 External examination for all measures of length												
§ (R 35-1)	Requirement	P	F	Remarks								
	be included in the nominal length of the measure.											
14.2.2	<div>The means of fastening a supplementary device to the end of a measure shall be permitted to obscure the scale marks at the beginning of the measure only under the following conditions:</div> <table><tr><td>Nominal length m</td><td>Length of scale marking that may be obscured</td></tr><tr><td>< 5</td><td>None</td></tr><tr><td>5≤L≤10</td><td>≤ first 15 mm</td></tr><tr><td>> 10</td><td>≤ first 30 mm</td></tr></table>	Nominal length m	Length of scale marking that may be obscured	< 5	None	5≤L≤10	≤ first 15 mm	> 10	≤ first 30 mm			
Nominal length m	Length of scale marking that may be obscured											
< 5	None											
5≤L≤10	≤ first 15 mm											
> 10	≤ first 30 mm											
14.2.3	For measures contained in a case that is designed to be part of the range of the scale:											
	- the zero end of the blade shall be of the end type.											
	- the blade shall be provided with a fixed or sliding hook or tongue.											
	- the case is correctly marked with its dimensions including the measuring unit symbol.											
14.2.4	- a belt clip or carrying strap, if fitted, must not obscure the case dimensions marked on the side of the case.											
14.2.4	- a belt clip or carrying strap, if fitted to a dimensioned case, must not interfere with internal measurements (i.e. must not prevent the end of the case touching the object being measured).											
14.2.5	The blade lock, if fitted, shall be strong enough to hold the blade at all extensions up to and including fully extended.											
14.2.6	The cross-section of the blade shall be cambered (i.e. the blade shall be of curved cross-section).											
14.3.1	These measures may have two scales with the same point of origin on the same face											
14.3.1	They may also have a scale on the											

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
	other face.			
14.3.2	The scale interval shall be less than or equal to 1 cm.			
14.4	These measures shall conform to accuracy class I or II.			
15	Semi-rigid steel tape measures in a case with digital readout			
15.1	These measures have nominal lengths between 0.5 and 15 metres. See 5.1 & 5.2 also.			
15.1	They shall be of the end, line, or composite type.			
15.2.1	If the zero end is of a squared end type and is fitted with a ring, this ring may be included in the nominal length of the measure.			
15.2.2	For measures contained in a case that is designed to be part of the range of the scale:			
	- the dimension of the case shall be indicated on the case.			
	- the zero end of the blade shall be of the end type.			
	- the blade shall be provided with a fixed or sliding hook or tongue.			
15.2.3	The blade lock, if fitted, shall be strong enough to hold the blade at all extensions up to and including fully extended.			
15.2.4	The cross-section of the blade shall be cambered (i.e. the blade shall be of curved cross-section).			
15.3.1	These measures may have two scales with the same point of origin on the same face			
15.3.1	They may also have a scale on the other face.			
15.3.2	The scale interval shall be less than or equal to 1 cm.			
15.4.1	The power source compartment shall form an integral part of the measure			
15.5	These measures shall conform to accuracy class I or II.			
16	One-piece rigid or semi-rigid measures			
16.1	These measures shall have nominal lengths between 0.5 and 5 metres.			

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
	See 5.1 & 5.2 also.			
16.1	They shall be of the end, line, or composite type.			
16.2.1	These measures shall be made of metal or other suitable materials.			
16.2.2	If the zero scale mark of a dipstick is its end, this end shall be provided with an impact and wear resistant heel or tip made of a material not liable to cause sparking on impact.			
16.3	These measures may have a scale on each of the two faces.			
16.4	These measures shall conform to accuracy class I or II.			
17	Flexible tape measures made of fibreglass and plastics or other suitable non-metallic materials			
17.1	These measures shall have nominal lengths between 0.5 and 5 metres. See 5.1 & 5.2 also.			
17.1	They shall be of the end, line, or composite type.			
17.2.1	The free ends of end or composite measures shall be provided with wear-resistant bands or tips which are firmly attached to the tape.			
17.2.2	End measures - one end may be fitted with a ring, which may be included in the nominal length of the measure.			
17.2.3	The specified tension shall be approximately 10 to 20 N, and shall be indicated on the measure.			
17.2.4	Line measures not fitted with a ring - the zero scale mark shall be located at a distance of at least 20 mm from the nearest end of the measure.			
17.2.4	Line measures fitted with a ring - the zero scale mark shall be located at a distance of at least 20 mm from the outer edge of the ring.			
17.3	These measures shall conform to accuracy class I, II or III.			
18	Folding measures made of metal or other materials			
18.1	These measures shall have nominal lengths between 0.5 and 5 metres. See 5.1 & 5.2 also.			

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
18.1	They shall be of the end type.			
18.2.1	All parts which are jointed at both ends shall have the same length between their jointing axes.			
18.2.2	Jointing and alignment of the unfolded measure shall be ensured by an effective device.			
18.2.2	The total additional error due to the jointing and alignment shall not exceed: ± 0.3 mm for measures of class II, ± 0.5 mm for measures of class III.			
18.3	These measures may have a scale on each of the two faces.			
18.4	These measures shall conform to accuracy class II or III.			
18.4	Accuracy class I is also permissible for screw-assembly type jointed measures.			
19	Telescopic measures made of metal or other materials			
19.1	These measures shall have nominal lengths between 0.5 and 5 metres. See 5.1 & 5.2 also.			
19.1	They shall be of the end type.			
19.2.1	Jointing and alignment of the unfolded measure shall be ensured by an effective device.			
19.2.2	These measures shall be made of metal or other suitable materials.			
19.2.2	The total additional error due to the jointing and alignment shall not exceed: ± 0.3 mm for measures of class II, ± 0.5 mm for measures of class III.			
19.2.3	The terminal surface of the measure shall be flat and perpendicular to the longitudinal axis of the measure.			
19.2.4	The end of the measure shall be provided with an impact and wear resistant heel or tip made of a material not liable to cause sparking on impact.			
19.3.1	Measures which are circular in cross-section shall have only one scale along their length.			

5.1.1 External examination for all measures of length										
§ (R 35-1)	Requirement	P	F	Remarks						
19.3.2	Measures which are rectangular in cross-section may have a scale on each of the two faces.									
19.4	These measures shall conform to accuracy class II or III.									
20	Telescopic measures made of metal or other materials with digital readout									
20.1 – 20.4	Same as 19.1 – 19.4									
20.5.1	If the digital readout is powered, the power source compartment shall form an integral part of the measure.									
	B — MEASURES FOR LONG LENGTHS									
21	Flexible steel tape measures with winding device not designed for measuring lengths greater than their nominal length by repeated use of the same tape									
21.1	These measures have nominal lengths between 5 and 200 metres. See 5.1 & 5.2 also.									
21.1	They shall be of the line or composite type.									
21.2.1	Class I - the free end shall be provided with a handle or ring, which is <i>not</i> included in the nominal length.									
21.2.1	Class II - the free end shall be provided with a handle or ring which <i>may</i> be included in the nominal length.									
21.2.2	The means of fastening a supplementary device to the end of a measure shall be permitted to obscure the scale marks at the beginning of the measure only under the following conditions: <table border="1"><tr><td>Nominal length m</td><td>Length of scale marking that may be obscured</td></tr><tr><td>5 ≤ L ≤ 10</td><td>≤ first 15 mm</td></tr><tr><td>>10</td><td>≤ first 30 mm</td></tr></table>	Nominal length m	Length of scale marking that may be obscured	5 ≤ L ≤ 10	≤ first 15 mm	>10	≤ first 30 mm			
Nominal length m	Length of scale marking that may be obscured									
5 ≤ L ≤ 10	≤ first 15 mm									
>10	≤ first 30 mm									
21.2.3	A belt clip or carrying strap, if fitted, must not obscure the dimensions marked on the side of the case.									
21.2.3	A belt clip or carrying strap, if fitted, must not interfere with internal measurements (i.e. must not prevent the end of the case touching the object being measured).									
21.2.4	The specified tension shall be									

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
	approximately 50 N or greater, and shall be indicated on the measure.			
21.3.1	These measures may have a scale on each of the two faces.			
21.3.2	The reference temperature, if other than 20°C, shall be indicated on the measure (see 10.2).			
21.4	These measures shall conform to accuracy class I or II.			
22	Flexible steel tape measures with tensioning weight or sinker			
22.1	These measures have nominal lengths between 5 and 50 metres. See 5.1 & 5.2 also.			
22.1	They shall be of the composite type.			
22.2	The mass of the sinker shall be indicated to within ± 10 grams, on both measure and sinker.			
22.3.1	The sinker shall have a sufficient mass to stretch out the tape properly.			
22.3.1	The sinker shall be made of a material not liable to cause sparking on impact.			
22.3.2	The sinker may be detachable or permanently attached to the tape.			
22.3.3	This attachment or joint shall be such that additional measurement uncertainty is minimised.			
22.3.4	The other end of the measure may be provided with a winding device.			
22.4	The scale shall be regular, with a scale interval of 1 millimetre.			
22.4	The base of the sinker shall constitute the principal scale mark at the zero end of the scale.			
22.4	The scale shall start on a flat face of the sinker and continue along the entire length of the tape.			
22.5	These measures shall conform to accuracy class I or II.			
23	Flexible steel tape measures with tensioning weight or sinker equipped with electronic sensing			
23.1	These measures have nominal lengths between 5 and 50 metres. See 5.1 & 5.2 also.			
23.1	They shall be of the composite type.			
23.2	The mass of the sinker shall be indicated to within ± 10 grams, on both			

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
	measure and sinker.			
23.3.1	The sinker shall have a sufficient mass to stretch out the tape properly.			
23.3.1	The sinker shall be made of a material not liable to cause sparking on impact.			
23.3.2	The sinker shall be permanently attached to the tape.			
23.3.2	This attachment or joint shall not introduce any uncertainty of measurement.			
23.3.3	The other end of the measure may be provided with a winding device.			
23.4	The scale shall be regular, with a scale interval of 1 millimetre.			
23.4	The base of the sinker shall constitute the principal scale mark at the zero end of the scale.			
23.4	The scale continues along the entire length of the tape.			
23.5	The sensing element of the measure shall provide a clear and reliable indication of the air/oil and oil/water phase transition.			
23.6.1	If the measure is powered by a replaceable or rechargeable battery, the battery compartment shall form an integral part of the measure.			
23.7	These measures shall conform to accuracy class I or II.			
23.7	With the electronic sensor fitted, the instrument shall conform to the accuracy classes and maximum permissible errors specified in OIML R85, 3.4.			
24	Flexible steel surveyor's tapes designed for measuring lengths greater than their nominal length by repeated use of the same tape			
24.1	These measures shall have nominal lengths of 5, 10, 20, 50, 100, or 200 metres.			
24.1	They shall be of the end or line type.			
24.2	The specified tension shall be approximately 50 N or greater, and shall be indicated on the measure.			
24.3	These measures shall be provided with handles or rings at both ends.			

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
24.3	If the handles are included in the nominal length of the measure, they shall be so constructed that their attachment to the tape introduces no uncertainty of measurement.			
24.4	These measures shall conform to accuracy class I or II.			
25	Flexible tape measures made of fibreglass and plastics or other suitable non-metallic materials			
25.1	These measures shall have nominal lengths between 5 and 100 metres. See 5.1 & 5.2 also.			
25.1	They shall be of the end, line, or composite type.			
25.2.1	End measures - the ends shall be provided with wear-resistant bands or tips which are firmly attached to the tape.			
25.2.1	Composite measures - the zero end shall be provided with a wear-resistant band or tip which is firmly attached to the tape.			
25.2.2	Class I measures - the free end may be provided with a ring, which is not included in the nominal length.			
25.2.2	Measures in class II and III - the free end may be provided with a ring which may be included in the nominal length. In this case, the beginning of the scale shall be clearly indicated.			
25.2.3	The means of fastening a supplementary device to the end of a measure shall be permitted to obscure the scale marks at the beginning of the measure only under the following conditions:			
	Nominal length m	Length of scale marking that may be obscured		
	$5 \leq L \leq 10$	\leq first 15 mm		
	> 10	\leq first 30 mm		
25.2.4	A belt clip or carrying strap, if fitted, must not obscure the dimensions marked on the side of the case.			
25.2.5	The specified tension shall be			

5.1.1 External examination for all measures of length				
§ (R 35-1)	Requirement	P	F	Remarks
	approximately 10 to 20 N and shall be indicated on the measure.			
25.3	These measures may have a scale on each of the two faces.			
25.4	These measures shall conform to accuracy class I, II or III.			

5.2 Checklist for accuracy tests

5.2.1 Accuracy tests for all measures				
§ (R 35-1)	Requirement	P	F	Remarks
26.2.2	Scale accuracy and large scale linearity			
	a) The error in the nominal length of the measure shall not exceed the mpe given in R35-1 4.2.1.			
	b) The error in the distance between two non-consecutive marks at four randomly-chosen points along the length of the measure plus the nominal length shall not exceed the mpe given in R35-1 4.2.1.			
26.2.3	Scale interval accuracy			
	The error in the length of the scale interval at four randomly-chosen points along the length of the measure and at the nominal length shall not exceed the mpe given in R35-1 4.2.2.			
26.2.4	Scale interval linearity			
	The error in the difference between the lengths of two consecutive scale intervals at four randomly-chosen points along the length of the measure and at the nominal length shall not exceed the mpe given in R35-1 4.2.3.			
26.2.5	Accuracy of other metrological components			
	The presence of the additional component shall not cause the error in the length of the blade to exceed the mpe given in 4.2.1 or the error in the length of the component, as a separate entity, shall not exceed the mpe.			
27.2	Accuracy tests for indicating devices			
27.2.2	Throughout the length of the blade, including zero, the length indicated on the display shall meet the requirement in R35-1, 11.1.6.			
27.2.3	For changes in blade extension of one scale interval, the length indicated on the display shall meet the requirement in R35-1, 11.1.6.			

5.3 Checklist for influence factor and disturbance tests for electronic devices fitted to material measures of length.

5.3.1 Performance tests for electronic devices fitted to material measures of length.				
§ (R 35-1)	Requirement	P	F	Remarks
27.5.1	Static temperatures (dry heat, cold)			
	During the application of the high and low temperatures: a. All functions shall operate as designed. b. There shall be no error in the indication of length during the application of the influence factor (see R35-1, 11.1.6)			
27.5.2	Damp heat, cyclic, condensing			
	After the application of the damp heat cycles and a recovery period: a. All functions shall operate as designed. b. There shall be no error in the indication of length (see R35-1, 11.1.6)			
27.5.2	Mechanical shock (drop test)			
	Following this test there shall be no error in the indication of length (R35-1, 11.1.6)			
27.5.4	Immunity against radiated, radio-frequency			
27.5.4.1	Electromagnetic fields of general origin			
	The length indicated on the display shall agree with the measurement made by the blade to the nearest scale interval of the blade (R35-1, 11.1.6) whilst the EUT is subjected to the electromagnetic radiation, at the same reference conditions.			
27.5.4.2	Electromagnetic fields specifically caused by digital radio telephones			
	The length indicated on the display shall agree with the measurement made by the blade to the nearest scale interval of the blade (R35-1, 11.1.6) whilst the EUT is subjected to the electromagnetic radiation, at the same reference conditions.			
27.5.5	Electrostatic discharge			
	There shall be no error in the indication of length during the application of the			

5.3.1 Performance tests for electronic devices fitted to material measures of length.				
§ (R 35-1)	Requirement	P	F	Remarks
	influence factor (see R35-1, 11.1.6)			
26.3.5	Voltage of battery power source			
	During the application of the voltage limits: a. All functions shall operate as designed. b. There shall be no error in the indication of length during the application of the influence factor (see R35-1, 11.1.6)			

6. Type evaluation tests (for all measures of length including those with additional electronic devices)

Application No: _____
 Model: _____
 Observer: _____

	At start	At end	
Temp.:			°C
Rel h.:			%
Date:			yyyy-mm-dd
Time:			hh:mm:ss

6.1 Datasheet for blade accuracy calculations

The datasheet shown below assumes that all measurements are made from the origin of the measure according to Figure 1 in R 35-2.

Position ¹	Reading on EUT blade		Reading on test equipment /
	a		b
	(m)		(m)
A ₁			
A ₂			
A ₃			
B ₁			
B ₂			
B ₃			
C ₁			
C ₂			
C ₃			
D ₁			
D ₂			
D ₃			
E ₁			
E ₂			
E ₃			
Nominal length			
Tension:		N	
Coefficient of thermal expansion		10 ⁻⁶ per °C	

¹ See R35-2, Figure 1

6.2 Scale accuracy and large scale linearity (R35-2, 7.4)

Error of EUT blade ²		Allowance for ends or jointing ³	Correction due to thermal expansion ⁴	Total error ⁵	mpe ⁶ (mm)	P	F
	α (mm)	β (mm)	γ (mm)	$\varepsilon = \alpha - \beta + \gamma$ (mm)			
$aA_1 - bA_1$							
$aB_1 - bB_1$							
$aC_1 - bC_1$							
$aD_1 - bD_1$							
$aE_3 - bE_3$ (Nominal length)							

☐

Passed

☐

Failed

Remarks:

² a and b refer to the columns in the table in 6.1.³ R35-1, 4.2.4, 18.2.2⁴ R35-2, 7.2.6.⁵ Note: Modulus value of α is used here.⁶ R35-1, Table 1, 21.6, 22.7

6.3 Scale interval accuracy (R35-2, 7.5)

Error of EUT blade		mpe ⁷	P	F
	(mm)	(mm)		
$(aA_2 - aA_1) - (bA_2 - bA_1)$				
$(aB_2 - aB_1) - (bB_2 - bB_1)$				
$(aC_2 - aC_1) - (bC_2 - bC_1)$				
$(aD_2 - aD_1) - (bD_2 - bD_1)$				
$(aE_2 - aE_1) - (bE_2 - bE_1)$				

☐

Passed

☐

Failed

Remarks:

⁷ R35-1, 4.2.2

6.4 Scale interval linearity (R35-2, 7.6)

Error of EUT blade		mpe ⁸	P	F
	(mm)	(mm)		
$[(aA_2 - aA_1) - (bA_2 - bA_1)] - [(aA_3 - aA_2) - (bA_3 - bA_2)]$				
$[(aB_2 - aB_1) - (bB_2 - bB_1)] - [(aB_3 - aB_2) - (bB_3 - bB_2)]$				
$[(aC_2 - aC_1) - (bC_2 - bC_1)] - [(aC_3 - aC_2) - (bC_3 - bC_2)]$				
$[(aD_2 - aD_1) - (bD_2 - bD_1)] - [(aD_3 - aD_2) - (bD_3 - bD_2)]$				
$[(aE_2 - aE_1) - (bE_2 - bE_1)] - [(aE_3 - aE_2) - (bE_3 - bE_2)]$				

☐

Passed

☐

Failed

Remarks:

6.5 Accuracy of other metrological components⁹ (R35-2, 7.7)

Application No: _____	Temp.: _____	At start	At end	°C
Model: _____	Rel h.: _____			%
Observer: _____	Date: _____			yyyy-mm-dd
	Time: _____			hh:mm:ss

6.5.1 Separable components, such as dimensioned tape case, sinker

Description of EUT component:

Apparent length of EUT component	Reading on test equipment /	Difference	mpe ^{10, 11}	P	F
a	b	(a-b)			
(mm)	(mm)	(mm)	(mm)		

⁸ IR35-1, 4.2.3, 4.2.4⁹ e.g. hook, ring dimensioned tape case, detachable sinker¹⁰ IR35-1, equation in 4.2.1¹¹ Sinker - see R35-1, 22.5.

Apparent length of EUT component	Reading on test equipment /	Difference	mpe ^{10, 11}	P	F
a	b	(a-b)			
(mm)	(mm)	(mm)	(mm)		

☐ Passed
 ☐ Failed

Remarks:

6.5.2 Attached components, such as hooks and rings

Description of EUT component:

Internal or external measurement?	Reading on EUT blade	Reading on test equipment /	Error	mpe	P	F
	a	b	a - b			
	(m)	(m)	(mm)	(mm)		

☐ Passed
 ☐ Failed

Remarks:

6.6 Indicating devices

6.6.1 Agreement with blade reading (R35-2, 7.8.1)

Position	Reading on EUT blade	Indication on EUT electronic device	Difference ¹²	P	F
	a	b	a-b		
	(m)	(m)	(mm)		
Zero	0				
A ₁					
B ₁					
C ₁					
D ₁					
E ₃					

☐

Passed

☐

Failed

Remarks:

6.6.2 Hysteresis (R35-2, 7.8.2)

For three positions randomly chosen along the blade, the length measured is increased by one scale interval and the indicated reading is recorded. The length measured is then decreased by one scale interval and the indicated reading is recorded.

Scale interval: mm

Position ¹³	Reading on EUT blade	Indication on EUT electronic device	Error ¹⁴		P	F
	a	b				
	(m)	(m)		(mm)		
A ₁						
A ₂			$(aA_2 - aA_1) - (bA_2 - bA_1)$			
A ₁			$(aA_1 - aA_2) - (bA_1 - bA_2)$			
B ₁						
B ₂			$(aB_2 - aB_1) - (bB_2 - bB_1)$			

¹² Difference is zero for correct operation.

¹³ The subscripts denote a change in position of one scale interval.

¹⁴ The error is zero for correct operation.

B_1			$(aB_1 - aB_2) - (bB_1 - bB_2)$			
C_1						
C_2			$(aC_2 - aC_1) - (bC_2 - bC_1)$			
C_1			$(aC_1 - aC_2) - (bC_1 - bC_2)$			

☐

Passed

☐

Failed

Remarks:

7. Tests for influence factors and disturbances

7.1 Static temperatures (specified high) (R 35-2, 8.6)

Application No: _____	Temp.: _____	At start	At end	°C
Model: _____	Rel h.: _____			%
Observer: _____	Date: _____			yyyy-mm-dd
	Time: _____			hh:mm:ss

Position ¹⁵	Reading on EUT blade	Indication on EUT electronic device	Error in indication	P	F
	a	b	b-a		
	(m)	(m)	(mm)		
A					
B					
C					
D					
E ₃					

<input type="checkbox"/>	Passed	<input type="checkbox"/>	Failed
--------------------------	--------	--------------------------	--------

Remarks:

¹⁵ R 35-2, Figure 1

7.2 Static temperatures (specified low) Cold (R 35-2, 8.6)

Application No: _____
 Model: _____
 Observer: _____

	At start	At end	
Temp.:			°C
Rel h.:			%
Date:			yyyy-mm-dd
Time:			hh:mm:ss

Position ¹⁶	Reading on EUT blade	Indication on EUT electronic device /	Error in indication	P	F
	a	b	b-a		
	(m)	(m)	(mm)		
A					
B					
C					
D					
E ₃					

☐

Passed

☐

Failed

Remarks:

¹⁶ R 35-2, Figure 1

7.3 Damp heat, cyclic (condensing) (R 35-2, 8.7)

Application No: _____
 Model: _____
 Observer: _____

	Peak	Trough	
Temp.:			°C
Rel h.:			%
Date:			yyyy-mm-dd
Time:			hh:mm:ss

Position ¹⁷	Reading on EUT blade	Indication on EUT electronic device /	Error in indication	P	F
	a	b	b-a		
	(m)	(m)	(mm)		
A					
B					
C					
D					
E ₃					

☐

Passed

☐

Failed

Remarks:

¹⁷ R 35-2, Figure 1

7.4 Mechanical shock (R35-2, 8.8)

Application No: _____
 Model: _____
 Observer: _____

	At start	At end	
Temp.:			°C
Rel h.:			%
Date:			yyyy-mm-dd
Time:			hh:mm:ss

Height of fall: m

Point of impact on EUT	Reading on EUT blade	Indication on EUT electronic device /	Error in indication	P	F
	a	b	b-a		
	(m)	(m)	(mm)		

Condition after test¹⁸:

☐ Passed ☐ Failed

Remarks:

¹⁸ e.g. Functional/non-functional, damage observed.

7.5 Radio-frequency immunity (R 35-2, 8.9)**7.5.1 Radiated, radio-frequency, electromagnetic fields of general origin (R 35-2, 8.9.1)**

Application No: _____	Temp.: _____	At start	At end	°C
Model: _____	Rel h.: _____			%
Observer: _____	Date: _____			yyyy-mm-dd
	Time: _____			hh:mm:ss

Rate of sweep: Load: Material load:

Disturbance				Result		
Antenna	Frequency range (MHz)	Polarisation	Facing EUT	Indication on EUT electronic device /	Significant fault	
					No	Yes (remarks)
Without disturbance						
		Vertical	Front			
			Right			
			Left			
			Rear			
		Horizontal	Front			
			Right			
			Left			
			Rear			
		Vertical	Front			
			Right			
			Left			
			Rear			
		Horizontal	Front			
			Right			
			Left			
			Rear			

Frequency range: 26 – 1000 MHz or 80 – 1000 MHz

Field strength: 3 or 10 V/m

Modulation: 80% AM, 1 kHz sine wave

☐

Passed

☐

Failed

Remarks:

7.5.2 Radiated, radio-frequency, electromagnetic fields specifically caused by digital radio telephones (R 35-2, 8.9.1)

Application No: _____	Temp.: _____	At start	At end	°C
Model: _____	Rel h.: _____			%
Observer: _____	Date: _____			yyyy-mm-dd
	Time: _____			hh:mm:ss

Rate of sweep: Load: Material load:

Disturbance				Result		
Antenna	Frequency range (MHz)	Polarisation	Facing EUT	Indication on EUT electronic device /	Significant fault	
					No	Yes (remarks)
Without disturbance						
		Vertical	Front			
			Right			
			Left			
			Rear			
		Horizontal	Front			
			Right			
			Left			
			Rear			
		Vertical	Front			
			Right			
			Left			
			Rear			
		Horizontal	Front			
			Right			
			Left			
			Rear			

Frequency range: 800 – 960 MHz or 1400 – 2000 MHz

Field strength: 10 or 30 V/m

Modulation: 80% AM, 1 kHz sine wave

Notes:

A 2 W GSM telephone typically produces a field strength of 10 V/m at a distance of 0.6 m. For an 8 W GSM this distance is 1.1 m.

☐ Passed ☐ Failed

Remarks:

7.6 Electrostatic Discharge (R 35-2, 8.10)

Application No: _____ Temp.: _____ At start _____ At end _____ °C
 Model: _____ Rel h.: _____ %
 Observer: _____ Date: _____ yyyy-mm-dd
 Time: _____ hh:mm:ss

☐ Contact discharges

☐ Air discharges Polarity¹⁹ ☐ pos ☐ neg

Discharges				Result		
Load	Test voltage (kV)	Number of discharges ≥ 10	Repetition interval (s)	Indication on EUT electronic device /	Significant fault	
					No	Yes (remarks, test points)
	Without disturbance					
	6					
	8 (air discharges)					

Notes: (1) The significant fault is if the indication changes from the value it had with no disturbance present.
 (2) Indicate test points of the EUT by photos or sketches, if necessary.
 (3) If the EUT fails, the test point at which this occurs shall be recorded.

☐ Passed ☐ Failed

Remarks:

¹⁹ IEC 61000-4-2 specifies that the test shall be conducted with the most sensitive polarity.

7.7 Voltage of battery power source (R 35-2, 8.11)

Application No: _____
 Model: _____
 Observer: _____

	At start	At end	
Temp.:			°C
Rel h.:			%
Date:			yyyy-mm-dd
Time:			hh:mm:ss

Type of power source specified for EUT:

Internal impedance of specified power source: ohm

Nominal voltage: V

Manufacturer's specified maximum voltage value (U_{max}): V

Manufacturer's specified maximum voltage value (U_{min}): V

High voltage test:

Applied high voltage: V

Performance of the EUT (please tick):

- ☐ Continues to function
- ☐ Goes blank
- ☐ Indicates an error signal
- ☐ Functions with errors
- ☐ Other (*please specify*):

Low Voltage test

Applied low voltage: V

Performance of the EUT (please tick):

- ☐ Continues to function
- ☐ Goes blank
- ☐ Indicates an error signal

☐ Functions with errors

☐ Other (*please specify*):

☐ Passed

☐ Failed

Remarks:

II. Initial verification report

The specific format layout for reporting initial verifications and subsequent verifications of material measures of length is left largely to the metrological authorities and the individual organizations carrying out verification tests. However, the report (records) shall contain the minimum information detailed in R 35-2, 11.2.2).

In addition to this any special requirements and/or restrictions for initial verification detailed in the type approval certificate for the EUT must be applied. A record of equipment and instrumentation used, together with calibration details, (see Annexes B & C) shall be kept.

The following basic information should also be included in the verification report (record) followed by the results of the tests (examples of how the report may be formatted are given below):

1. Information concerning the EUT verified

Category of measure:

Sub-category of measure:

Description of EUT:

Model number:

Nominal length:

Accuracy class:

Year of manufacture:

The manufacturer:

Authorized representative:

Address:

Testing laboratory:

Authorized representative:

Address:

2. Initial verification test report (R 35-2, 11.2.2)

2.1 Example 1

Approved material measure of length (no additional electronic devices)

Approval No:	_____	Temp.:	At start	At end	°C
Model:	_____	Rel h.:			%
Observer:	_____	Date:			yyyy-mm-dd
		Time:			hh:mm:ss

Tests for initial verification

Test	Number of test points ²⁰
Scale accuracy and large scale linearity	Nominal length + two intermediate points
Scale interval accuracy	1
Scale interval linearity	1
Accuracy of other metrological components	1

²⁰ Where marginal results justify it, the test laboratory may increase the number of points.

Results of tests

Sampling plan²¹: Single / Double (*delete as necessary*)

Inspection level:

Actual size of lot:

Sample size code letter:

Recommended sample size:

AQL:

Acceptance number: First: ²² Second: ²³

Rejection number: First: Second:

Test	Actual number of rejects		Reasons for rejection
	First	Second	
Visual inspection			
Scale accuracy and large scale linearity			
Scale interval accuracy			
Scale interval linearity			
Accuracy of other metrological components ²⁴ (specify):			
Total number of rejects for lot:			
Accept/reject lot:			

²¹ See OIML R35-2, 10.1, ISO 2859-1

²² Single sampling plan or first sample of double sampling plan

²³ Second sample of double sampling plan

²⁴ E.g. dimensioned tape case, sinker.

Comments:

2.2 Example 2

Approved material measure of length (with additional electronic devices)

Approval No:	_____	Temp.:	At start	At end	°C
Model:	_____	Rel h.:			%
Observer:	_____	Date:			yyyy-mm-dd
		Time:			hh:mm:ss

Tests for initial verification

Test	Number of test points ²⁵
Scale accuracy and large scale linearity	Nominal length + two intermediate points
Scale interval accuracy	1
Scale interval linearity	1
Accuracy of other metrological components	1
Indicating device – agreement/hysteresis	1

²⁵ Where marginal results justify it, the test laboratory may increase the number of points.

Results of tests

Sampling plan²⁶: Single / Double (*delete as necessary*)

Inspection level:

Actual size of lot:

Sample size code letter:

Recommended sample size:

AQL:

Acceptance number: First:²⁷ Second:²⁸

Rejection number: First: Second:

Test	Actual number of rejects		Reasons for rejection
	First	Second	
Visual inspection			
Scale accuracy and large scale linearity			
Scale interval accuracy			
Scale interval linearity			
Accuracy of other metrological components ²⁹ (specify):			
Indicating device – agreement with blade reading			

²⁶ See OIML R35-2, 10.1, ISO 2859-1

²⁷ Single sampling plan or first sample of double sampling plan

²⁸ Second sample of double sampling plan

²⁹ E.g. dimensioned tape case, sinker.

Indicating device – hysteresis			
Total number of rejects for lot:			
Accept/reject lot:			

Comments:

Annex A

(Mandatory)

List of documents received from the manufacturer concerning the type (R35-2, 5)

[illegible]

Annex B

(Mandatory)

List of test equipment used in examinations and tests

[illegible]

Annex C
(Mandatory, when applicable)

List of simulators used in examinations and tests

System or module name	Reference number	Function
Comments:		

Simulator description and drawings, block diagram, etc., should be attached to the report, if available.