

Member/ Organisation	Page number	Document clause	Comments	Proposed change
UK	9, 5, 11,13, etc.	0.1.3, 2.5, 2.7.4.3, 2.8.5, 3.4.6, 3.9.3, 0.2.11.2. 0.3.7, 4.5.4,etc	Editorial, Spacing between words required, for example: In 0.1.3, “ typeis ” should be “type is” In 0.3.7, “minimum totalized load,Σmin In 2.5, “not exceed35 % of” In 0.2.11.2, [OIML R 60][7] In 4.5.4, “...that information for at least5 minutes...”	Amend text spacing errors here and in other parts of the terminology section.
UK	28	2.7.5.3 Discrimination of the totalization indicating device used for zero totalization	Editorial: Remove strikethrough from the last 2 bulletin: c) 0.4 % for class 1; d) 0.2 % for class 2.	Amend to: c) 0.1 % for class 1; d) 0.2 % for class 2.
UK	40	5.1.6.6	Editorial: $v_{min} \leq \text{Max}/(S \times R/$	Amend to: $v_{min} \leq \text{Max}/(S \times R/\sqrt{N})$
UK	49	A.3.7.3	Editorial: Spacing between text required. MPE0.35 %	Amend to: MPE 0.35 %

Member/ Organisation	Page number	Document clause	Comments	Proposed change
UK	50	A.5.2	Editorial: Double full stop at the end of the second paragraph. ...shall be conducted. .	Delete one full stop.
UK	59	A.7.2.3.2 Number of test cycles	Editorial: Please remove this requirement as it is in contradiction with the requirement in Table 6a. At least two test cycles are conducted: Test 1: At reference temperature and 50 %R.H. immediately before the cyclic humidity test start. Test 2: At reference temperature and 95 %R.H. immediately after the last cycle has ended.	Delete requirement.
UK	70	A.7.3.5.1, A.7.3.5.2 Test information:	Editorial: In accordance with the note is A.7.3.5, ...	Amend to: In accordance with the note is in A.7.3.5, ...
UK	76	A.9.1.2 Maximum variation during zero-load test (2.8.4)	Editorial: First paragraph is highlighted in yellow.	Remove yellow highlight from first paragraph.